

# Wireless transport module for PT1000 sensor (DLTa-tr-P1000)

DLTa-tr-P1000



- Accurate wireless detection
- Battery life of over 6 years
- Compatible with all Wireless Value Base Stations
- Range 1,600 metres (clear line of sight)

- Features e-ink display and programmable button for transport start and end time

# Wireless transport module for PT1000 sensor (DLTa-tr-P1000)

DLTa-tr-P1000



## Description

### DLTa-tr-P1000

Wireless transport sensor for temperature using a PT1000 element

Thanks to its e-ink display and button, this sensor is ideal for monitoring temperature during transport. The temperature can be read continuously on the energy-efficient display. Pressing the button at the start and end of transport places markers in the graph, making the transport clearly visible for analysis. The sensor's large internal storage ensures no data is lost if the connection to the Base Station is interrupted for any reason. The measurement results from this sensor can then be used for monitoring and analysis in the Online Portal.

- Memory to store 10,000 measurements
- Adjustable measurement interval
- Attractive IP65 ABS enclosure
- Suitable for wall mounting
- Existing system can easily be expanded with additional sensors
- Battery replaceable by user
- Unique network ID to avoid interference with other wireless systems

# Wireless transport module for PT1000 sensor (DLTa-tr-P1000)

DLTa-tr-P1000

## Specifications

### General

|              |                                                                                                |
|--------------|------------------------------------------------------------------------------------------------|
| Battery type | AA                                                                                             |
| Casing       | IP65                                                                                           |
| Battery life | over 6 years                                                                                   |
| Model        | Wireless module suitable for external Pt1000 sensor with e-ink display and programmable button |

### Measurement range

|                  |                                                            |
|------------------|------------------------------------------------------------|
| Temperature      | -100 °C to +200 °C, optionally up to +400 °C at extra cost |
| Operating limits | -20°C to +80°C                                             |
| Signal range     | 1,600 meters with clear line of sight                      |

### Measurement accuracy

|             |                             |
|-------------|-----------------------------|
| Temperature | +/- 0.1°C (excluding probe) |
|-------------|-----------------------------|

### Measurement resolution

|             |        |
|-------------|--------|
| Temperature | 0.1 °C |
|-------------|--------|

### Legislation and standards

|                                 |     |
|---------------------------------|-----|
| RED (Radio Equipment Directive) | yes |
| CE                              | yes |
| EN 300 220                      | yes |

### Technical specifications

|                 |                     |
|-----------------|---------------------|
| Battery voltage | 3.6                 |
| IP rating       | IP65                |
| Memory          | 10,000 measurements |

### Dimensions

|                    |                              |
|--------------------|------------------------------|
| Housing dimensions | 105 (l) x 70 (w) x 34 (h) mm |
| Weight             | 93 g (excluding battery)     |